



### QMFZ2.E84716 Plastics - Component

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

### Plastics - Component

[See General Information for Plastics - Component](#)

**LORD CORPORATION**  
111 LORD DR  
CARY, NC 27511 USA

E84716

									H	D	
		Min.		H	H	R T I			V	4	C
		Thk	Flame	W	A	Elec	Mech		T	9	T
Material Dsg	Color	mm	Class	I	I		Imp	Str	R	5	I
<b>Epoxy Casting Compound (EP - Casting), potting, furnished as two liquid components.</b>											
340/70	BK	0.27	HB	-	-	90	90	90	-	-	-
6006-HS/6011	BK	6.4-7.0	V-0	-	-	90	90	90	-	-	-
6007	BK	6.0	V-0	-	-	90	90	90	-	-	-
6009	YL, RD, BK	6.0	V-0	-	-	90	90	90	-	-	-
6035	BK, GN	6.0	V-0	-	-	90	90	90	-	-	-
6055	BK	1.5	HB	-	-	90	90	90	-	-	-
6066	BK	6.0	V-0	-	-	90	90	90	-	-	-
6071	BL	1.5	HB	-	-	90	90	90	-	-	-
6074	BK	1.5	HB	-	-	90	90	90	-	-	-
6075	BK	6.1-6.6	V-0	-	-	90	90	90	-	-	-
6077/AB	BK	3.0	V-0	-	-	90	90	90	-	-	-
EP-236	NC	3.0	V-0	1	1	90	90	90	-	4	0
		-	-	-	-	-	-	-			
ES-36	BK	3.0	V-0	-	-	90	90	90	-	-	-
<b>Polyurethane (PUR), furnished as two liquid components.</b>											
UR-288	BK	3.0	HB	-	-	50	50	50	-	-	-
		6.0	HB	-	-	50	50	50			
UR-388	BK	3.0	HB	-	0	50	50	50	0	-	0
		3.0	V-2	-	0	50	50	50			
		9.0	V-0	-	0	50	50	50			
		12.0	V-0	0	0	50	50	50			
UR-388 FAST	BK	3.0	HB	-	0	50	50	50	0	-	0
		3.0	V-2	-	0	50	50	50			
		9.0	V-0	-	0	50	50	50			
		12.0	V-0	0	0	50	50	50			
<b>Silicone "Room Temperature Vulcanizing" (RTV), "Circalok", furnished as two liquid components.</b>											
6710/6730	RD	3.0	-	-	0	105	105	105	0	-	0
		6.0	V-0	-	-	105	105	105			
		9.0	V-0	-	-	105	105	105			
<b>Silicone (SI), "Gelease", furnished as bulk.</b>											
MG-121	GY	1.5	V-0	-	-	105	105	105	-	-	-

		3.0	V-0	-	-	105	105	105			
<b>Silicone (SI), furnished as two liquid components.</b>											
<b>6701</b>	CL	6.5	HB	-	-	150	150	150	-	-	-
<b>6702</b>	RD	6.0	V-0	-	-	150	150	150	-	-	-
<b>6703</b>	GY	6.0	V-0	-	-	150	150	150	-	-	-
<b>6705</b>	GY	6.0	V-0	-	-	150	150	150	-	-	-
<b>6706</b>	GY	6.0	V-0	-	-	150	150	150	-	-	-
<b>6707</b>	GY	3.0	V-0	-	-	150	150	150	-	-	-
<b>6714</b>	GN	6.0	V-0	-	-	105	105	105	-	-	-
<b>SC-104</b>	GY	6.3	V-0	-	-	150	-	150	-	-	-
<b>SC-114</b>	BK	1.5	V-1	-	-	150	-	150	-	-	-
		3.0	V-0	-	-	150	-	150			
<b>SC-218</b>	BK	1.5	HB	3	-	150	150	150	0	4	0
		3.0	HB	2	0	150	150	150			
		6.0	V-1	1	0	150	150	150			
		9.0	V-0	1	0	150	150	150			
<b>SC-284</b>	GY	2.9-3.2	V-0	-	-	150	-	150	-	-	-
<b>SC-303</b>	GY	1.5	-	-	-	200	-	190	-	-	-
		3.2	-	-	-	200	-	200			
		6.0	V-0	-	-	200	-	200			
<b>SC-305</b>	BK	1.5	-	-	0	170	-	170	1	4	0
		3.0	-	2	0	170	-	170			
		6.0	V-1	1	0	170	-	170			
		9.0	V-1	1	0	170	-	170			
		12.0	V-0	0	0	170	-	170			
<b>SC-308</b>	RD	3.4 - 3.7	V-0	-	-	150	150	150	-	-	-
	GY	6.1	V-0	-	-	150	150	150			
<b>SC-309</b>	GY	2.76-3.02	V-0	-	-	180	-	180	-	-	0
<b>SC-310</b>	GY	5.73-6.21	V-0	-	-	150	-	150	-	-	-
<b>SC-313</b>	GY	3.3 - 3.6	V-0	-	-	150	-	150	-	-	-
<b>SC-314</b>	PK	2.9 - 3.1	V-0	-	-	150	150	150	-	-	-
<b>SC-315</b>	GY	1.5	V-1	1	0	150	-	150	0	4	0
		3.0	V-0	1	0	150	-	150			
		6.0	V-0	0	-	150	-	150			
<b>SC-320 LV</b>	PK	3.2-3.5	V-0	-	-	150	-	150	-	-	-
<b>SC-320 LV(H)</b>	PK	1.5	-	0	0	150	-	150	0	3	0
		3.0	V-0	0	0	150	-	150			
		6.0	V-0	0	-	150	-	150			
<b>SC-320 THK</b>	PK	1.5	-	-	-	180	-	180	-	-	-
		3.2	V-0	-	-	180	-	180			
<b>SC-320, SC-320 SLW</b>	PK	1.5	-	-	-	180	-	180	-	-	-
		3.2	V-0	-	-	180	-	180			
<b>SC-321</b>	GY	2.8-3.1	V-0	-	-	150	150	150	-	-	-
<b>Unsaturated Polyester (UP), furnished as two liquid components.</b>											
<b>PR-81</b>	ALL	3.3	V-0	-	-	105	130	130	-	-	-

Marking: Company name or tradename "Circalok" , "Lord" and material designation on container, wrapper or finished part.  
 Last Updated on 2017-01-20

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".